

Date \_\_\_\_\_

Name \_\_\_\_\_

Client \_\_\_\_\_



Project Name \_\_\_\_\_

Quote# \_\_\_\_\_

Type/Quantity \_\_\_\_\_

**FLIP TWIN SET 40**  
**217 61 40 4202**

[Weblink](#)



Cutout shape/size:	148 mm
Recessed depth:	225 mm
Available colors:	ALU GREY (217 61 40 4202 A) GREY BROWN (217 61 40 4202 G)
ADJUSTABLE	
INCL.2 x POWERLED WHITE 6,2W / CRI>80 / 3000K / 703lm	
INCL.LED POWER SUPPLY 350 mA-DC	
LED Technics:	Light source: 1406 lm // 12.4 W // 113 lm/W Luminaire: 1187 lm // 14 W // 83 lm/W
220-240V / 50-60Hz	
Class:	I
Weight:	1.7 KG
Protection level:	IP54/IP67
Minimum distance:	n.a.
Options:	IP68 CONNECTION KIT IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual. [217\\_61\\_25\\_4202\\_02\\_HAND.pdf](#)


**FLIP TWIN SET 40**

217 61 40 4202

**Related references**


**WATERPROOF CONNECTION PARTS**

[Weblink / Specsheel](#)



IP68 CONNECTION KIT  
216 12 01

[Weblink / Specsheel](#)



IP68 CONNECTOR 3P  
216 12 02